

TILES_{Wall}

Technical Datasheet Polished & Soft Tiles

20

Years Pro
Rata
Warranty

Dimension	thickness (d)	$\pm 0,5 \text{ mm} \cdot d_{\text{max}} - d_{\text{min}} \leq \pm 0,5 \text{ mm}$
	length	$\pm 1 \text{ mm}$
	width (b)	$\pm 0,25 \text{ mm} \cdot b_{\text{max}} - b_{\text{min}} \leq \pm 0,25 \text{ mm}$

Polished Packing Information

Size(mm)	Pieces	QuantityPerBoxes(m2)
300X300	16	1.44
300x600	8	1.44
600X600	4	1.44
2600X600	1	1.56
1200X600	2	1.44
1500X750	2	2.25
800X800	2	1.28

Polished Technical Specification

Water absorption	ISO 10545-3	0.07%
Chemical resistance	ISO 10545-13	Complies with standards
Stain resistance	ISO 10545-14	Class 5
DryTest	AS 4586	D1
Wet Pendulum Test	AS 4586	P1

Soft Packing Information

Size(mm)	Pieces	QuantityPerBoxes(m2)
300X300	16	1.44
300x600	8	1.44
600X600	4	1.44
2600X600	1	1.56
1200X600	2	1.44
1500X750	2	2.25
800X800	2	1.28

Polished Technical Specification

Water absorption	ISO 10545-3	0.04%
Chemical resistance	ISO 10545-13	Complies with standards
Stain resistance	ISO 10545-14	Class 5
DryTest	AS 4586	D1
Wet Pendulum Test	AS 4586	P1